

# FlowThru

## RIDGE VENT

**ATTIC PROTECTION**  
by Quarrix.



Installation videos,  
NFA Calculator & Tips,  
Warranty & Patents



PART #	#58777	#58780	#62466	#62477	#58778	#58779	#58879	#58878
STYLE	Roll	Roll	Section	Section	Section	Section	Section	Section
LENGTH	20' 6.1 m	20' 6.1 m	4' 1.22 m	4' 1.22 m	4' 1.22 m	4' 1.22 m	4' 1.22 m	4' 1.22 m
WIDTH	11¼" 28.58 cm	9" 22.86 cm	11¼" 28.58 cm	9" 22.86 cm	11¼" 28.58 cm	11¼" 28.58 cm	9" 22.86 cm	9" 22.86 cm
HEIGHT	5/8" 15.875 mm	5/8" 15.875 mm	1" 25.4 mm	1" 25.4 mm	5/8" 15.875 mm	5/8" 15.875 mm	5/8" 25.4 mm	5/8" 15.875 mm
NFA sq in	12.7	12.7	19	19	12.7	12.7	12.7	12.7
SLOPE/PITCH	3:12 - 20:12	3:12 - 20:12	3:12 - 20:12	3:12 - 20:12	3:12 - 20:12	3:12 - 20:12	3:12 - 20:12	3:12 - 20:12
NAILS			2½" nails	2½" nails		1¾" coil nails		1¾" coil nails
MATERIAL	HDPE Plastic							
ROOF MATERIAL	Asphalt Shingles, Standing Seam Metal, Cedar Shakes, Slate, and Flat Tile.							

Not suggested for use in cold weather climates that receive an average annual snowfall of 10" or greater (including AK, CO, CT, DE, ID, IL, IN, IA, KS, KY, ME, MD, MA, MI, MN, MT, NE, NH, NJ, NY, ND, OH, PA, RI, SD, UT, VT, VA, WV, WI, WY). StormStop ridge vent is recommended for these climate regions.

# FlowThru

## RIDGE VENT

Long-lasting protection that keeps air flowing in the attic for a healthy home.


### › FEATURES & APPLICATIONS



Clog-Free Design



Gun-Nailable



Durable HDPE



Maximum Airflow